UL iQ™ 25/05/14 19:32

for enhanced search functionality please visit UL's iQ™ family of databases

Component - Plastics E59481

## **CHANG CHUN PLASTICS CO LTD**

7TH FL, 301 SONGKIANG RD, TAIPEI 104 TW

## **T651**

Phenolic Molding Compound (PMC), "LONGLITE", furnished as pellets or powder

	Min Thk	Flame			RTI	RTI	RTI		
Color	(mm)	Class	HWI	HAI	Elec	lmp	Str		
NC, BK, GN	1.6-1.7	V-0	1	4	150	150	150		
Comparative Tracking Index (CTI): 3			Inclined Plane Tracking (IPT): -						
Dielectric Streng	Dielectric Strength (kV/mm): - Volume Resistivity (10 <sup>x</sup> ohm-cm)		nm-cm): -						
High-Voltage Arc Tracking Rate (HVTR):		High Volt, Low Current Arc Resis (D495): 5							
Dimensional S	Stability (%): -								

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2006-03-29 Last Revised: 2006-03-28

© 2014 UL LLC



## **IEC and ISO Test Methods**

	Inickness				
<b>Test Method</b>	Units	Tested (mm)	Value		
IEC 60695-11-10	Class (color)	1.6-1.7	V-0 (NC, BK, GN)		
IEC 60695-2-12	C	-	-		
IEC 60695-2-13	С	-	-		
IEC 60112	Volts (Max)	-	-		
IEC 60695-10-2	С	-	-		
ISO 75-2	С	-	-		
ISO 527-2	MPa	-	-		
ISO 178	MPa	-	-		
ISO 8256	kJ/m <sup>2</sup>	-	-		
ISO 180	kJ/m <sup>2</sup>	-	-		
ISO 179-2	kJ/m <sup>2</sup>	-	-		
	IEC 60695-11-10 IEC 60695-2-12 IEC 60695-2-13 IEC 60112 IEC 60695-10-2 ISO 75-2 ISO 527-2 ISO 178 ISO 8256 ISO 180	IEC 60695-11-10	Test Method Units Tested (mm) IEC 60695-11-10 Class (color) 1.6-1.7 IEC 60695-2-12 C - IEC 60695-2-13 C - IEC 60112 Volts (Max) - IEC 60695-10-2 C - ISO 75-2 C - ISO 527-2 MPa - ISO 178 MPa - ISO 8256 kJ/m² - ISO 180 kJ/m² -		

© 2014 UL LLC

The materials covered in this database are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE PRODUCTS SUBMITTED TO UNDERWRITERS LABORATORIES.

Notice of Disclaimer