

iq.ul.com

Component - Plastics [\[guide info\]](#)

E107536

SHINKONG SYNTHETIC FIBERS CORP

223 YEN PING RD SEC 3, PIN CHENG TAOYUAN HSIEN 324 TW

D202G30@

Polybutylene Terephthalate (PBT), glass reinforced, furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC, BK	0.3	V-0	4	0	75	75	75
ALL	0.71	V-0	3	0	140	120	140
	1.5	V-0	2	0	140	130	140
	3.0	V-0	0	0	140	130	140

Comparative Tracking Index (CTI): 3
 Dielectric Strength (kV/mm): 23
 High-Voltage Arc Tracking Rate (HVTR): 4
 Dimensional Stability (%): -

Inclined Plane Tracking (IPT): -
 Volume Resistivity (10^X ohm-cm): 15
 High Volt, Low Current Arc Resis (D495): 6

@ - Ball pressure temperature of 200 deg. C, tested in accordance with IEC 695.10.2 and IEC 950 5.4.2

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1987-07-13

Last Revised: 2006-11-28

© 2016 UL LLC

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	0.3	V-0 (NC, BK)
			0.71	V-0 (ALL)
			1.5	V-0 (ALL)
			3.0	V-0 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	3.0	200
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-