# Need more information? Click Here to go to the UL iQ<sup>™</sup> for Plastics database

**Component - Plastics** 

#### **HUAFON GROUP CO LTD**

#### 1688 KAIFAQU ROAD, ECONOMIC DEVELOPMENT ZONE, RUIAN ZHEJIANG 325200 CN

## **EP158N**

#### Polyamide 66 (PA66), furnished as pellets

Color	Min Thk (mm)	Flame Class	нш	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.0	V-2			65	65	65
ALL	1.0	V-2	-	-	00	60	60
	3.0	V-2	-	-	65	65	65
Comparative	Tracking Index (CT	I): -		Inclined	d Plane Trac	king (IPT):	-
Dielec	tric Strength (kV/mm	n): <b>-</b>	Ň	Volume Res	sistivity (10 <sup>x</sup>	ohm-cm) :	-
High-Volta	age Arc Tracking Ra (HVTR		High Vo	olt, Low Cur	rent Arc Re	sis (D495):	-
Dim	ensional Stability (%	b): -					

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2012-09-28

Last Revised: 2012-09-28

## © 2013 UL LLC



E355539

# **IEC and ISO Test Methods**

			Inickness	
Test Name	Test Method	Units	Tested (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.0	V-2 (ALL)
			3.0	V-2 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	С	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	С	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	С	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	С	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-

#### © 2013 UL LLC

The materials covered in this database are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE PRODUCTS SUBMITTED TO UNDERWRITERS LABORATORIES.

Notice of Disclaimer